

## Modèle Stealth

### Pression/Couple Table Conversion

Pression PSI - bar	XXI-1	XXI-3	XXI-5
	Couple en M/kg		
1500 - 104	23	66	116
1600 - 110	25	71	124
1800 - 124	28	81	140
2000 -138	31	91	156
2200 - 152	35	100	172
2400 - 165	38	110	189
2600 - 179	42	119	206
2800 - 193	45	129	222
3000 - 207	48	138	239
3200 - 220	52	148	256
3400 - 234	56	157	272
3600 - 248	59	167	289
3800 - 262	63	176	306
4000 - 276	66	186	323
4200 - 290	70	196	340
4400 - 303	74	205	357
4600 - 317	78	215	374
4800 - 331	82	225	391
5000 - 345	86	234	407
5200 - 358	89	244	425
5400 - 372	93	253	442
5600 - 386	97	262	459
5800 - 400	101	271	476
6000 - 414	104	281	493
6200 - 427	108	290	510
6400 - 441	112	298	527
6600 - 455	116	307	544
6800 - 468	120	316	561
7000 - 482	124	325	578
7200 - 496	129	334	595
7400 - 510	133	343	611
7600 - 524	137	352	628
7800 - 538	141	362	644
8000 - 552	145	371	661
8200 - 565	149	378	677
8400 - 579	153	386	694
8600 - 593	156	394	711
8800 - 607	160	402	728
9000 - 620	163	409	744
9200 - 634	168	417	761
9400 - 648	172	425	777
9600 - 662	176	433	794
9800 - 676	180	440	810
10000 - 690	184	448	827

