

HYTORC

TOOL MODEL: VERSA-8 W SLIM HEX LINK (LINK SIZES #2-3)
PRESSURE/TORQUE CONVERSION CHART FOR HEX SIZES UP TO 2 3/8"

Standard Torque Chart

PRESSURE IN PSI	TORQUE IN			PRESSURE IN BAR
	FT. LBS.	KGM	NM	
1500	1295	179	1756	104
1600	1388	192	1881	110
1800	1573	218	2132	124
2000	1758	243	2383	138
2200	1933	267	2621	152
2400	2109	292	2859	165
2600	2284	316	3097	179
2800	2460	340	3334	193
3000	2635	364	3572	207
3200	2817	390	3819	220
3400	2999	415	4066	234
3600	3181	440	4312	248
3800	3363	465	4559	262
4000	3545	490	4806	276
4200	3722	515	5046	290
4400	3899	539	5286	303
4600	4077	564	5526	317
4800	4254	588	5767	331
5000	4431	613	6007	345
5200	4607	637	6245	358
5400	4783	661	6484	372
5600	4959	686	6722	386
5800	5135	710	6961	400
6000	5311	734	7199	414
6200	5489	759	7440	427
6400	5666	784	7681	441
6600	5844	808	7923	455
6800	6022	833	8164	468
7000	6200	857	8405	482
7200	6380	882	8649	496
7400	6560	907	8893	510
7600	6740	932	9137	524
7800	6920	957	9381	538
8000	7100	982	9625	552
8200	7273	1006	9859	565
8400	7446	1030	10093	579
8600	7618	1054	10327	593
8800	7791	1077	10561	607
9000	7963	1101	10795	620
9200	8140	1126	11035	634
9400	8317	1150	11275	648
9600	8494	1175	11515	662
9800	8671	1199	11754	676
10000	8848	1224	11994	690