

HYTORC

TOOL MODEL:HY-STEALTH 22 with HEX LINK

PRESSURE/TORQUE CONVERSION CHART

Standard Torque Chart

PRESSURE IN	TORQUE IN			PRESSURE IN
PSI	FT. LBS.	KGM	NM	BAR
1500	3250	449	4406	104
1600	3472	480	4707	110
1800	3916	542	5309	124
2000	4360	603	5910	138
2200	4802	664	6510	152
2400	5244	725	7109	165
2600	5686	786	7708	179
2800	6128	848	8307	193
3000	6570	909	8906	207
3200	7000	968	9489	220
3400	7430	1028	10072	234
3600	7860	1087	10655	248
3800	8290	1147	11238	262
4000	8720	1206	11821	276
4200	9132	1263	12379	290
4400	9544	1320	12938	303
4600	9956	1377	13496	317
4800	10368	1434	14055	331
5000	10780	1491	14613	345
5200	11245	1555	15244	358
5400	11710	1619	15874	372
5600	12175	1684	16504	386
5800	12640	1748	17135	400
6000	13105	1812	17765	414
6200	13542	1873	18357	427
6400	13979	1933	18949	441
6600	14415	1994	19542	455
6800	14852	2054	20134	468
7000	15289	2114	20726	482
7200	15729	2175	21323	496
7400	16169	2236	21919	510
7600	16610	2297	22516	524
7800	17050	2358	23113	538
8000	17490	2419	23709	552
8200	17928	2479	24303	565
8400	18366	2540	24897	579
8600	18804	2601	25491	593
8800	19242	2661	26084	607
9000	19680	2722	26678	620
9200	20119	2782	27273	634
9400	20558	2843	27868	648
9600	20997	2904	28464	662
9800	21436	2965	29059	676
10000	21875	3025	29654	690