

HYTORC

TOOL MODEL: HY-30XLCT W/ HEX LINK PRESSURE/TORQUE CONVERSION CHART

Standard Torque Chart

| PRESSURE IN PSI | TORQUE IN | | | PRESSURE IN BAR |
|--------------------|-----------|------|-------|--------------------|
| | FT. LBS. | KGM | NM | |
| 1500 | 4579 | 633 | 6207 | 104 |
| 1600 | 4890 | 676 | 6629 | 110 |
| 1800 | 5513 | 762 | 7473 | 124 |
| 2000 | 6135 | 848 | 8317 | 138 |
| 2200 | 6759 | 935 | 9163 | 152 |
| 2400 | 7383 | 1021 | 10009 | 165 |
| 2600 | 8008 | 1107 | 10855 | 179 |
| 2800 | 8632 | 1194 | 11701 | 193 |
| 3000 | 9256 | 1280 | 12547 | 207 |
| 3200 | 9881 | 1367 | 13395 | 220 |
| 3400 | 10506 | 1453 | 14242 | 234 |
| 3600 | 11132 | 1540 | 15090 | 248 |
| 3800 | 11757 | 1626 | 15938 | 262 |
| 4000 | 12382 | 1712 | 16785 | 276 |
| 4200 | 13001 | 1798 | 17624 | 290 |
| 4400 | 13620 | 1884 | 18463 | 303 |
| 4600 | 14239 | 1969 | 19302 | 317 |
| 4800 | 14858 | 2055 | 20142 | 331 |
| 5000 | 15477 | 2140 | 20981 | 345 |
| 5200 | 16105 | 2227 | 21832 | 358 |
| 5400 | 16733 | 2314 | 22683 | 372 |
| 5600 | 17361 | 2401 | 23535 | 386 |
| 5800 | 17989 | 2488 | 24386 | 400 |
| 6000 | 18617 | 2575 | 25237 | 414 |
| 6200 | 19230 | 2660 | 26068 | 427 |
| 6400 | 19843 | 2744 | 26899 | 441 |
| 6600 | 20456 | 2829 | 27730 | 455 |
| 6800 | 21069 | 2914 | 28561 | 468 |
| 7000 | 21682 | 2999 | 29392 | 482 |
| 7200 | 22299 | 3084 | 30228 | 496 |
| 7400 | 22916 | 3169 | 31064 | 510 |
| 7600 | 23532 | 3255 | 31901 | 524 |
| 7800 | 24149 | 3340 | 32737 | 538 |
| 8000 | 24766 | 3425 | 33573 | 552 |
| 8200 | 25408 | 3514 | 34443 | 565 |
| 8400 | 26050 | 3603 | 35313 | 579 |
| 8600 | 26692 | 3692 | 36184 | 593 |
| 8800 | 27334 | 3780 | 37054 | 607 |
| 9000 | 27976 | 3869 | 37924 | 620 |
| 9200 | 28578 | 3952 | 38740 | 634 |
| 9400 | 29180 | 4036 | 39556 | 648 |
| 9600 | 29782 | 4119 | 40372 | 662 |
| 9800 | 30384 | 4202 | 41189 | 676 |
| 10000 | 30986 | 4285 | 42005 | 690 |